



# PSP 300x Casing Replacement

Written By: kbrunner



## INTRODUCTION

Steps for replacing the outer casing of a Sony PSP-3000.



### TOOLS:

- [Phillips #00 Screwdriver](#) (1)
- [Spudger](#) (1)



### PARTS:

- [Sony PSP 3000 Front Case](#) (1)
-

## Step 1 — Battery



- Place the PSP face down and locate the battery cover on the left side of the device.
- Lift and remove the battery cover to reveal the battery.
- Remove the battery.

## Step 2 — Casing



- Peel back the warranty sticker that is behind the battery with a spudger or your fingernail.



## Step 3




- Unscrew all four screws from the back of the PSP with the Phillips #00 Screwdriver.
  - Two are located behind the battery's warranty sticker.
  - Two are located on the right side of the PSP.

## Step 4



- Next, unscrew the two screws located at the top of the PSP.

## Step 5



- Then, remove the single screw from the bottom edge of the PSP (which is positioned next to the barcode).

## Step 6



- Slide the spudger in between the outer casing of the PSP, beginning at the "R" shoulder button, and gently pry off the casing.
- Remove the front casing completely.

To reassemble your device, follow these instructions in reverse order.

This document was last generated on 2017-06-16 06:24:54 PM.